TPO Bonding Adhesive Data Sheet

Updated: 5/10





Ever Guard TPOSINGLE-PLY BOOFING SYSTEMS

Description

EverGuard® Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single-ply roofing membranes and flashings to various roofing substrates. Everguard® Bonding Adhesive is a general purpose rubber-based bonding adhesive for attaching TPO based single-ply membranes to various substrates, including polyisocyanurate insulation, and gypsum based cover boards

Features and Benefits

- Excellent coverage up to 70 sq ft per gallon bonded membrane
- Fast drying solvent system
- Easy application using roller or brush
- Spray application also possible
- High initial tack

Physical Properties

Base: Synthetic polymer **Solvent:** Hydrocarbon blend **Flash Point:** 0°F (-18°C) **Weight/Gallon:** 7.28 lbs

Color: Yellow

Viscosity: 2,300 - 2,700 cps **Coverage:** 50-70 sq. ft./gallon

Total Solids: 25% +/- 2.5%

Voc: 611 grams/liter

Shelf Life: 1 year, unopened Open Time: Up to 60 minutes Dry Time: 5 – 15 minutes

Application: Roller, brush or spray



TPO Bonding Adhesive

Ordering Information

Item Number: 778000M Packaging: 5 gallon pails Weight: 37lbs/pail

Shipping: 45 pails per pallet

Quality You Can Trust Since 1886... From North America's Largest Roofing Manufacturer™